

7400R

Solid carbide corner radius TIALN coated end-mill, center cutting, for processing hard metals, high-end surface finish.



- Milling geometry
- 4 Flutes
- Corner Radius
- 37° Angle
- Finish

Standard Length

øD	ød	L1	L	øR	Serial
3	3	6	50	0.5	7403006050R05
3	3	6	50	1	7403006050R10
4	4	8	50	0.5	7404008050R05
4	4	8	50	1	7404008050R10
4	4	8	50	1.5	7404008050R15
5	5	10	57	0.5	7405010057R05
5	5	10	57	1	7405010057R10
5	5	10	57	1.5	7405010057R15
5	5	10	57	2	7405010057R20
6	6	12	57	0.5	7406012057R05
6	6	12	57	1	7406012057R10
6	6	12	57	1.5	7406012057R15
6	6	12	57	2	7406012057R20
6	6	12	57	2.5	7406012057R25
7	7	14	63	0.5	7407014063R05
7	7	14	63	1	7407014063R10
7	7	14	63	1.5	7407014063R15
7	7	14	63	2	7407014063R20
7	7	14	63	2.5	7407014063R25
7	7	14	63	3	7407014063R30
8	8	16	63	0.5	7408016063R05
8	8	16	63	1	7408016063R10
8	8	16	63	1.5	7408016063R15
8	8	16	63	2	7408016063R20
8	8	16	63	2.5	7408016063R25
8	8	16	63	3	7408016063R30
8	8	16	63	3.5	7408016063R35
9	9	18	75	0.5	7409018075R05
9	9	18	75	1	7409018075R10
9	9	18	75	1.5	7409018075R15
9	9	18	75	2	7409018075R20
9	9	18	75	2.5	7409018075R25
9	9	18	75	3	7409018075R30
9	9	18	75	3.5	7409018075R35
9	9	18	75	4	7409018075R40
10	10	20	75	0.5	7410020075R05

øD	ød	L1	L	øR	Serial
10	10	20	75	1	7410020075R10
10	10	20	75	1.5	7410020075R15
10	10	20	75	2	7410020075R20
10	10	20	75	2.5	7410020075R25
10	10	20	75	3	7410020075R30
10	10	20	75	3.5	7410020075R35
10	10	20	75	4	7410020075R40
10	10	20	75	4.5	7410020075R45
12	12	24	83	0.5	7412024083R05
12	12	24	83	1	7412024083R10
12	12	24	83	1.5	7412024083R15
12	12	24	83	2	7412024083R20
12	12	24	83	2.5	7412024083R25
12	12	24	83	3	7412024083R30
12	12	24	83	3.5	7412024083R35
12	12	24	83	4	7412024083R40
12	12	24	83	4.5	7412024083R45
12	12	24	83	5	7412024083R50
12	12	24	83	5.5	7412024083R55
14	14	28	88	0.5	7414028088R05
14	14	28	88	1	7414028088R10
14	14	28	88	1.5	7414028088R15
14	14	28	88	2	7414028088R20
14	14	28	88	2.5	7414028088R25
14	14	28	88	3	7414028088R30
14	14	28	88	3.5	7414028088R35
14	14	28	88	4	7414028088R40
14	14	28	88	4.5	7414028088R45
14	14	28	88	5	7414028088R50
14	14	28	88	5.5	7414028088R55
14	14	28	88	6	7414028088R60
14	14	28	88	6.5	7414028088R65
16	16	32	92	0.5	7416032092R05
16	16	32	92	1	7416032092R10
16	16	32	92	1.5	7416032092R15
16	16	32	92	2	7416032092R20
16	16	32	92	2.5	7416032092R25
16	16	32	92	3	7416032092R30
16	16	32	92	3.5	7416032092R35
16	16	32	92	4	7416032092R40
16	16	32	92	4.5	7416032092R45
16	16	32	92	5	7416032092R50
16	16	32	92	5.5	7416032092R55

øD	ød	L1	L	øR	Serial
16	16	32	92	6	7416032092R60
16	16	32	92	6.5	7416032092R65
16	16	32	92	7	7416032092R70
16	16	32	92	7.5	7416032092R75
18	18	36	100	1	7418036100R10
18	18	36	100	2	7418036100R25
18	18	36	100	3	7418036100R35
18	18	36	100	4	7418036100R45
18	18	36	100	5	7418036100R55
18	18	36	100	6	7418036100R60
18	18	36	100	7	7418036100R70
18	18	36	100	8	7418036100R80
20	20	40	110	1	7420040110R10
20	20	40	110	2	7420040110R20
20	20	40	110	3	7420040110R30
20	20	40	110	4	7420040110R40
20	20	40	110	5	7420040110R50
20	20	40	110	6	7420040110R60
20	20	40	110	7	7420040110R70
20	20	40	110	8	7420040110R80
20	20	40	110	9	7420040110R90
22	22	44	125	1	7422044125R10
22	22	44	125	2	7422044125R20
22	22	44	125	3	7422044125R30
22	22	44	125	4	7422044125R40
22	22	44	125	5	7422044125R50
22	22	44	125	6	7422044125R60
22	22	44	125	7	7422044125R70
22	22	44	125	8	7422044125R80
22	22	44	125	9	7422044125R90
22	22	44	125	10	7422044125R100
25	25	50	125	1	7325050125R10
25	25	50	125	2	7425050125R20
25	25	50	125	3	7425050125R30
25	25	50	125	4	7425050125R40
25	25	50	125	5	7425050125R50
25	25	50	125	6	7425050125R60
25	25	50	125	7	7425050125R70
25	25	50	125	8	7425050125R80
25	25	50	125	9	7425050125R90
25	25	50	125	10	7425050125R100
25	25	50	125	11	7425050125R110
25	25	50	125	12	7425050125R120

כרסומי גמר רדיוס פינה מצופה TIALN, מצח חוזר מרכז, לעיבוד חומרים קשים בטיבי שטח גבוהים.

- Lengths according to demand
- Shank relieve according to demand
- Corner radius according to demand

- אורכים לפי דרישה
- שחרור קנה לפי דרישה
- רדיוס לפי דרישה