



7300R

Solid carbide corner radius end-mill, center cutting, for processing soft metals, high end surface finish.



- Milling geometry
- 3 Flutes
- Corner Radius
- 45° Angle
- Finish

Standard Length

øD	ød	L1	L	øR	Serial
3	3	6	50	0.5	7303006050R05
3	3	6	50	1	7303006050R10
4	4	8	50	0.5	7304008050R05
4	4	8	50	1	7304008050R10
4	4	8	50	1.5	7304008050R15
5	5	10	57	0.5	7305010057R05
5	5	10	57	1	7305010057R10
5	5	10	57	1.5	7305010057R15
5	5	10	57	2	7305010057R20
6	6	12	57	0.5	7306012057R05
6	6	12	57	1	7306012057R10
6	6	12	57	1.5	7306012057R15
6	6	12	57	2	7306012057R20
6	6	12	57	2.5	7306012057R25
7	7	14	63	0.5	7307014063R05
7	7	14	63	1	7307014063R10
7	7	14	63	1.5	7307014063R15
7	7	14	63	2	7307014063R20
7	7	14	63	2.5	7307014063R25
7	7	14	63	3	7307014063R30
8	8	16	63	0.5	7308016063R05
8	8	16	63	1	7308016063R10
8	8	16	63	1.5	7308016063R15
8	8	16	63	2	7308016063R20
8	8	16	63	2.5	7308016063R25
8	8	16	63	3	7308016063R30
8	8	16	63	3.5	7308016063R35
9	9	18	75	0.5	7309018075R05
9	9	18	75	1	7309018075R10
9	9	18	75	1.5	7309018075R15
9	9	18	75	2	7309018075R20
9	9	18	75	2.5	7309018075R25
9	9	18	75	3	7309018075R30
9	9	18	75	3.5	7309018075R35
9	9	18	75	4	7309018075R40
10	10	20	75	0.5	7310020075R05

øD	ød	L1	L	øR	Serial
10	10	20	75	1	7310020075R10
10	10	20	75	1.5	7310020075R15
10	10	20	75	2	7310020075R20
10	10	20	75	2.5	7310020075R25
10	10	20	75	3	7310020075R30
10	10	20	75	3.5	7310020075R35
10	10	20	75	4	7310020075R40
10	10	20	75	4.5	7310020075R45
12	12	24	83	0.5	7312024083R05
12	12	24	83	1	7312024083R10
12	12	24	83	1.5	7312024083R15
12	12	24	83	2	7312024083R20
12	12	24	83	2.5	7312024083R25
12	12	24	83	3	7312024083R30
12	12	24	83	3.5	7312024083R35
12	12	24	83	4	7312024083R40
12	12	24	83	4.5	7312024083R45
12	12	24	83	5	7312024083R50
12	12	24	83	5.5	7312024083R55
14	14	28	88	0.5	7314028088R05
14	14	28	88	1	7314028088R10
14	14	28	88	1.5	7314028088R15
14	14	28	88	2	7314028088R20
14	14	28	88	2.5	7314028088R25
14	14	28	88	3	7314028088R30
14	14	28	88	3.5	7314028088R35
14	14	28	88	4	7314028088R40
14	14	28	88	4.5	7314028088R45
14	14	28	88	5	7314028088R50
14	14	28	88	5.5	7314028088R55
14	14	28	88	6	7314028088R60
14	14	28	88	6.5	7314028088R65
16	16	32	92	0.5	7316032092R05
16	16	32	92	1	7316032092R10
16	16	32	92	1.5	7316032092R15
16	16	32	92	2	7316032092R20
16	16	32	92	2.5	7316032092R25
16	16	32	92	3	7316032092R30
16	16	32	92	3.5	7316032092R35
16	16	32	92	4	7316032092R40
16	16	32	92	4.5	7316032092R45
16	16	32	92	5	7316032092R50
16	16	32	92	5.5	7316032092R55

øD	ød	L1	L	øR	Serial
16	16	32	92	6	7316032092R60
16	16	32	92	6.5	7316032092R65
16	16	32	92	7	7316032092R70
16	16	32	92	7.5	7316032092R75
18	18	36	100	1	7318036100R10
18	18	36	100	2	7318036100R25
18	18	36	100	3	7318036100R35
18	18	36	100	4	7318036100R45
18	18	36	100	5	7318036100R55
18	18	36	100	6	7318036100R60
18	18	36	100	7	7318036100R70
18	18	36	100	8	7318036100R80
20	20	40	110	1	7320040110R10
20	20	40	110	2	7320040110R20
20	20	40	110	3	7320040110R30
20	20	40	110	4	7320040110R40
20	20	40	110	5	7320040110R50
20	20	40	110	6	7320040110R60
20	20	40	110	7	7320040110R70
20	20	40	110	8	7320040110R80
20	20	40	110	9	7320040110R90
22	22	44	125	1	7322044125R10
22	22	44	125	2	7322044125R20
22	22	44	125	3	7322044125R30
22	22	44	125	4	7322044125R40
22	22	44	125	5	7322044125R50
22	22	44	125	6	7322044125R60
22	22	44	125	7	7322044125R70
22	22	44	125	8	7322044125R80
22	22	44	125	9	7322044125R90
22	22	44	125	10	7322044125R100
25	25	50	125	1	7325050125R10
25	25	50	125	2	7325050125R20
25	25	50	125	3	7325050125R30
25	25	50	125	4	7325050125R40
25	25	50	125	5	7325050125R50
25	25	50	125	6	7325050125R60
25	25	50	125	7	7325050125R70
25	25	50	125	8	7325050125R80
25	25	50	125	9	7325050125R90
25	25	50	125	10	7325050125R100
25	25	50	125	11	7325050125R110
25	25	50	125	12	7325050125R120

כרסומי גמר רדיוס פינה ללא ציפוי, מצח חוזר מרכז, לעיבוד חומרים רכים בטיבי שטח גבוהים.

- Lengths according to demand
- Shank relieve according to demand
- Corner radius according to demand

- אורכים לפי דרישה
- שחרור קנה לפי דרישה
- רדיוס לפי דרישה