



# 7500

Solid carbide TiAlN coated end-mill, center cutting, for processing hard metals, high-end surface finish.



 Milling geometry

 5 Flutes

 38°~40° Angle

 Finish

 Standard Length

øD	ød	L1	L	Serial
6.0	6.0	16	57	7506016057
6.0	6.0	16	76	7506016075
6.0	6.0	16	100	7506016100
8.0	8.0	20	63	7508020063
8.0	8.0	20	100	7508020100
8.0	8.0	20	125	7508020125
10.0	10.0	22	75	7510022075
10.0	10.0	30	100	7510030100
10.0	10.0	40	100	7510040100
10.0	10.0	20	125	7510020125
12.0	12.0	25	83	7512025083
12.0	12.0	30	100	7512030100
12.0	12.0	40	100	7512040100
12.0	12.0	30	125	7512030125
12.0	12.0	30	160	7512030160
16.0	16.0	35	92	7516035092
16.0	16.0	35	100	7516035100
16.0	16.0	40	125	7516040125
16.0	16.0	40	160	7516040160
18.0	18.0	38	100	7518038100
18.0	18.0	38	125	7518038125
18.0	18.0	38	160	7518038160
20.0	20.0	40	110	7520040110
20.0	20.0	40	125	7520040125
20.0	20.0	40	160	7520040160
25.0	25.0	38	110	7525038110
25.0	25.0	45	125	7525045125
25.0	25.0	45	160	7525045160



- Lengths according to demand
- Shank relieve according to demand

כרסומי גמר פינה חדה מצופה TiAlN, מצח חוזר מרכז, לעיבוד חומרים קשים בטיבי שטח גבוהים.

- אורכים לפי דרישה
- שחרור קנה לפי דרישה