



Think Faster.

The best roughing-finish with variable helix and flute is now even better.



SR

Solid carbide 3-flutes, variable helix, radial OD, super polish end mill, prevents material from chipping on its cutting edge. For high velocity chip removal applications while keeping high-end surface finish. Designated for Aluminum processing.

Standard Length

ØD	Ød	L1	L2	L	ØR	Serial
6.0	6.0	14	-	57	0.2	SR-D6-57
6.0	6.0	14	-	75	0.2	SR-D6-75
6.0	6.0	14	-	100	0.2	SR-D6-100
6.0	6.0	14	-	125	0.2	SR-D6-125
8.0	8.0	16	30	63	0.25	SR-D8-63
8.0	8.0	16	40	75	0.25	SR-D8-75
8.0	8.0	16	40	100	0.25	SR-D8-100
8.0	8.0	16	40	125	0.25	SR-D8-125
10.0	10.0	18	32	75	0.3	SR-D10-75
10.0	10.0	18	42	100	0.3	SR-D10-100
10.0	10.0	18	40	125	0.3	SR-D10-125
12.0	12.0	20	35	83	0.35	SR-D12-83
12.0	12.0	20	45	100	0.35	SR-D12-100
12.0	12.0	20	45	125	0.35	SR-D12-125
16.0	16.0	26	40	92	0.4	SR-D16-92
16.0	16.0	26	50	100	0.4	SR-D16-100
16.0	16.0	26	50	130	0.4	SR-D16-130
16.0	16.0	26	50	160	0.4	SR-D16-160
20.0	20.0	34	60	110	0.5	SR-D20-110
20.0	20.0	34	60	125	0.5	SR-D20-125
20.0	20.0	34	60	160	0.5	SR-D20-160



כרוסום מתק"ש 3 להבים, מצח חודר מרכז, ספירלה משתנה, זווית חיתוך רדיאלית, השחזת ליטוש מבריקה למניעת היזבקות חומר. מתאים לפינוי חומר מהיר ויעיל תוך קבלת טיבי שטח מעולים. לעיבוד אלומיניום.

- Lengths according to demand
- Shank relieve according to demand
- Can be ordered with a chip breaker

- אורכים לפי דרישה
- שחרור קנה לפי דרישה
- ניתן להזמין עם שובר שבב



Follow Us!



#Shredder