

7300

Solid carbide end-mill, center cutting, for processing soft metals, high-end surface finish.



- Milling geometry
- 3 Flutes
- 45° Angle
- Finish

Standard Length

øD	ød	L1	L	Serial
1.0	1.0	6	50	7301006050
1.0	3.0	3	50	7301003050
1.0	3.0	6	50	7301006050
1.5	3.0	6	50	7301503050
1.5	6.0	6	57	7301506057
2.0	2.0	6	50	02006050D2
2.0	2.0	10	50	02010050D2
2.0	3.0	6	50	7302006050
2.0	3.0	10	50	7302010050
2.0	6.0	6	57	7302006057
2.0	6.0	10	57	7302010057
2.5	2.5	6	50	7302506050
2.5	3.0	6	50	7302506050
2.5	3.0	10	50	7302010050
2.5	6.0	6	57	7302506057
2.5	6.0	10	57	7302510057
3.0	6.0	6	57	7303006057
3.0	6.0	10	57	7303010057
3.0	6.0	12	57	7303012057
3.0	3.0	12	50	7303012050
3.0	3.0	10	63	7303010063
3.0	3.0	12	75	7303012075
3.0	3.0	20	75	7303020075
3.0	3.0	30	75	7303030075
3.0	3.0	14	100	7303014100
3.5	3.5	10	50	7303510050
3.5	6.0	8	57	7303508057
3.5	6.0	12	57	7303512057
4.0	6.0	8	57	7304008057
4.0	6.0	14	57	7304014057
4.0	4.0	12	50	7304012050
4.0	4.0	14	63	7304014063
4.0	4.0	20	75	7304020075
4.0	4.0	30	75	7304030075
4.0	4.0	14	100	7304014100
4.0	4.0	30	100	7304030100

כרסומי גמר פינה חדה ללא ציפוי,
מצח חודר מרכז, לעיבוד חומרים רכים
בטיבי שטח גבוהים.

- אורכים לפי דרישה
- שחרור קנה לפי דרישה

øD	ød	L1	L	Serial
4.5	6.0	10	57	7304510057
5.0	5.0	14	57	7305014057
5.0	6.0	14	57	7305014057D6
5.0	5.0	16	75	7305016075
5.0	5.0	16	100	7305016100
5.0	5.0	30	100	7305030100
5.0	5.0	16	125	7305016125
6.0	6.0	16	57	7306016057
6.0	6.0	16	63	7306016063
6.0	6.0	22	63	7306022063
6.0	6.0	22	75	7306022075
6.0	6.0	30	75	7306030075
6.0	6.0	20	100	7306020100
6.0	6.0	30	100	7306030100
6.0	6.0	40	100	7306040100
6.0	6.0	20	125	7306020125
6.0	6.0	20	160	7306020160
7.0	7.0	20	63	7307020063
7.0	7.0	30	100	7307030100
7.0	7.0	30	125	7307030125
7.0	7.0	30	160	7307030160
8.0	8.0	22	63	7308022063
8.0	8.0	30	75	7308030075
8.0	8.0	22	100	7308022100
8.0	8.0	30	100	7308030100
8.0	8.0	40	100	7308040100
8.0	8.0	50	100	7308050100
8.0	8.0	22	125	7308022125
8.0	8.0	60	125	7308060125
8.0	8.0	30	160	7308030160
8.0	8.0	30	200	7308030200
9.0	9.0	22	75	7309022075
9.0	9.0	30	100	7309030100
9.0	9.0	30	125	7309030125
10.0	10.0	24	75	7310024075
10.0	10.0	30	75	7310030075
10.0	10.0	30	100	7310030100
10.0	10.0	40	100	7310040100
10.0	10.0	50	100	7310050100
10.0	10.0	30	125	7310030125
10.0	10.0	60	125	7310060125
10.0	10.0	30	160	7310030160
10.0	10.0	30	200	7310030200
12.0	12.0	30	83	7312030083
12.0	12.0	30	100	7312030100

øD	ød	L1	L	Serial
12.0	12.0	40	100	7312040100
12.0	12.0	50	100	7312050100
12.0	12.0	30	125	7312030125
12.0	12.0	60	125	7312060125
12.0	12.0	30	160	7312030160
12.0	12.0	60	160	7312060160
12.0	12.0	30	200	7312030200
14.0	14.0	32	88	7314032088
14.0	14.0	40	100	7314040100
14.0	14.0	40	125	7314040125
14.0	14.0	60	125	7314060125
14.0	14.0	40	160	7314040160
14.0	14.0	40	200	7314040200
16.0	16.0	32	92	7316032092
16.0	16.0	42	100	7316042100
16.0	16.0	50	110	7316050110
16.0	16.0	42	125	7316042125
16.0	16.0	65	125	7316065125
16.0	16.0	42	160	7316042160
16.0	16.0	60	160	7316060160
16.0	16.0	85	160	7316085160
16.0	16.0	38	180	7316038160
16.0	16.0	38	200	7316038200
16.0	16.0	38	230	7316038230
16.0	16.0	38	250	7316038250
18.0	18.0	42	100	7318042100
18.0	18.0	42	125	7318042125
18.0	18.0	42	160	7318042160
18.0	18.0	42	200	7318042100
20.0	20.0	42	110	7320042110
20.0	20.0	42	125	7320042125
20.0	20.0	65	125	7320065125
20.0	20.0	42	160	7320042160
20.0	20.0	85	160	7320085160
20.0	20.0	42	180	7320042180
20.0	20.0	50	200	7320050200
20.0	20.0	50	250	7320050250
22.0	22.0	44	125	7322044125
22.0	22.0	44	160	7322044160
22.0	22.0	44	200	7322044200
25.0	25.0	50	125	7325050125
25.0	25.0	50	160	7325050160
25.0	25.0	50	200	7325050200
25.0	25.0	50	250	7325050250
25.0	25.0	50	330	7325050330

- Lengths according to demand
- Shank relieve according to demand